

# ONLREORFASSO: Start Online Reorder Associator for Files

The ONLREORFASSO function starts an online process to reorder the Associator of the specified files.

## Notes:

1. The online reorder process does not change the existing file extents but only reorganizes the file's index within these extents.
2. The online index reorder process does not move index elements out of blocks that are full (according to the Asso padding factor); it only moves elements into blocks that are not full.
3. Released index blocks are put into the unused RABN chain, which can be viewed using the ADAICK ICHECK utility function.

```
ADADBS ONLREORFASSO FILE = file-number  
[ASSOPFAC = asso-padding-factor]  
[PASSWORD = password ]  
[NOUSERABEND]  
[TEST]  
[WAIT]
```

This chapter covers the following topics:

- Essential Parameters
- Optional Parameters
- Example

---

## Essential Parameters

### FILE: File Number

FILE specifies the file to which the parameters that follow in the statement sequence apply.

Several files and their related parameters may be specified within one ONLREORFASSO operation. In this case, the files are reordered in the specified sequence.

If a component file of an Adabas expanded file is specified, only that file's Associator is reordered; this has no adverse effect on the other component files.

The Adabas checkpoint or security file number must not be specified.

## Optional Parameters

### **ASSOPFAC: Associator Padding Factor**

ASSOPFAC defines the Associator block padding factor, which is the percentage of each Associator block *not* used during the reorder process. Specify a value in the range 1-90. The number of bytes free after padding must be greater than the largest descriptor value plus 10.

If this parameter is omitted, the current padding factor in effect for the file is used.

### **PASSWORD: File Password**

If the file is password-protected, use this parameter to specify the password.

### **NOUSERABEND: Termination Without ABEND**

When an error is encountered while the function is running, the utility prints an error message and terminates with user ABEND 34 (with a dump) or user ABEND 35 (without a dump).

If NOUSERABEND is specified, the utility does *not* ABEND after printing the error message. Instead, the message "utility TERMINATED DUE TO ERROR CONDITION" is displayed and the utility terminates with condition code 20.

### **TEST: Test Syntax**

The TEST parameter tests the operation syntax without actually performing the operation. Only the syntax of the specified parameters can be tested; not the validity of values and variables.

### **WAIT: Wait for End of Process**

Specify WAIT if ADADBS is to wait for the end of the online process before proceeding either with the next function or with termination.

If WAIT is not specified, ADADBS proceeds immediately after initiating the online process.

## Example

Initiate an online process that reorders the Associator of file 10 first and then file 11. The Associator padding factor of file 11 is to be 5 percent.

```
ADADBS ONLREORFASSO FILE=10
ADADBS                FILE=11,ASSOPFAC=5
```